



Baureihen NO-BREAK KS® 400V/50Hz

Typ	Leistung		Abmaße Aggregat			Gewicht (kg)	Kraftstoff- verbrauch l/h
	kVA	kW	L (mm)	B (mm)	H (mm)		
NO-BREAK KS®4	150	120	4300	1700	2170	6560	34
NO-BREAK KS®5	200	160	4300	1700	2170	6560	45
NO-BREAK KS®5	300	240	4600	1700	2170	7256	66
NO-BREAK KS®5	400	320	5000	1700	2150	10227	86
NO-BREAK KS®5	500	400	5000	1700	2150	10227	106
NO-BREAK KS®5	630	504	6200	1700	1900	14707	143
NO-BREAK KS®5	700	560	6200	1700	1900	14707	160
NO-BREAK KS®5	800	640	6500	1700	1900	15838	186
NO-BREAK KS®5	900	720	5800	1700	1900	14876	195
NO-BREAK KS®5	1000	800	6250	1700	1900	15191	212
NO-BREAK KS®5	1250	1000	6750	1950	2400	22638	272
NO-BREAK KS®5	1500	1200	6750	1950	2400	22638	292
NO-BREAK KS®5	1750	1400	7500	1950	2400	26268	360
NO-BREAK KS®5	2000	1600	7500	1950	2400	26268	470
NO-BREAK KS®7e	2500	2000	9303	2000	2450	36870	560
NO-BREAK KS®7e	2750	2200	9303	2000	2450	36870	575

Andere Spannungsebenen auf Anfrage